

Click Here



There is a lot in common if you're looking for the USSD code for loans in Nigeria like I am because we have a list of all loans from loan apps, banks, telecommunications providers, and more. Online borrowing was formerly unthinkable, but thanks to advancements in technology, financial institutions are springing up everywhere to fill in major gaps. Yes, you may use your mobile device to apply for a quick internet loan in Nigeria without any collateral in as little as 5 minutes. That's why we compiled a list of the top 10 best loan apps in Nigeria, all of which offer loans with minimal hassle and paperwork. We all require financial credit for many reasons, including rent, school expenses, debt repayment, and so on. It might be aggravating to find oneself in such a financial bind. What if you know all the USSD code for loans in Nigeria? I mean, all you have to do is grab your smartphone, dial a few numbers, and then follow the prompt messages, and voila! You now have fast access to a mobile loan in Nigeria. In this article, we'll show you how to secure a loan in Nigeria using USSD codes. The USSD (Unstructured Supplementary Service Data) USSD allows you to make a smartphone-to-smartphone connection to use banking through predefined codes, also called quick codes. With USSD Banking, you can use your phone to carry out financial transactions using short, rapid codes. There is no requirement for an internet connection; all that is needed is a cellular network. With USSD banking, you make a nearby kind of financial transaction from money transfers to airtime purchases. More importantly, loans can be obtained using USSD codes. We wrote this article regarding the USSD code for loans in Nigeria for that reason. The process of applying for a loan using USSD is simple. All you have to do is: Know from whom you are borrowing. Obtain the effective USSD code. Every requirements must be met type The code in. Follow the directions exactly. Obtain a loan The table below shows major banks USSD codes to dial in Nigeria to get personal loans. Commercial Banks USSD Codes to Dial Guaranty Trust Bank Loan Code *737*51*51# Fidelity Bank Loan Code *770*First Bank Loan Code *894*EcoBank USSD Code *945*Skye Bank Loan Code *833* Sterling Bank Loan Code *822# Diamond Bank Loan Code *710*11# Eco Bank Loan Code *326# Diamond Access Loan Code *901*11# FCBM Loan Code *389# Unity Bank Loan Code *799# UBA Bank Loan Code *919# Union Bank Loan Code *826# Heritage Bank Loan Code *322# Keystone Bank Loan Code *533# Kwik Cash USSD Code *561# Migo Loan Code *901*Zenith Bank Loan Code *966# Isnt this amazing? The following table shows the list of mobile loan codes to get quick cash in Nigeria. It includes Nigerian telecommunication companies USSD codes to borrow money in Nigeria. Lending Institution Code to Dial AB Microfinance Bank Code *389*755# Access Bank payday Loan *901*11# Accion MFB *572*6# Airtel quick cash loan *561# Aledin nano *903*9# mobile loan code *561#. Fairmoney ussd code *322*6# FCBM Loan code *329# Glo cash loan code *322*1*04225701# Amount#GTBank loan code *737*51*51# InterSwitch loan *322# Kwik cash USSD code *561# Migo loan code *561# Mtn cash loan code *606*4# Trader Money loan code *540# Paga Loan code *242# Quick Teller (Mtn, Airtel, 9mobile) *322# Carbon Paylater USSD code *1303# Did you know there are more loan companies to get loan via USS code? The majority of these loan organizations have their custom-made mobile loan apps available for smartphone access to loans. Here are some frequently asked questions and answers about getting loans in Nigeria using USSD codes. There are two ways to go about it. You can request Quick Credit instantly by dialing *737*51*51# Quick Credit is also available on all GTBank online and mobile banking platform. Internet Banking GTWorld and GTBank Mobile App) Reply: Top 10 Highest currencies in Africa Dial *606# and select XtraTime. You can then select your preferred amount from the list. After selecting your preferred amount, the system will then send you a message with the amount you are about to borrow and the applicable service fee for you to confirm the transaction. Use the GTB loan code *737*8*2# With the mobile banking code and Uba quick loan code *919# you can apply for easy online loans without collateral on your registered number with Uba Bank. To activate and use the UBA mobile banking service without an ATM card, dial the UBA code transfer *919# and follow the instructions on the screen to get the PIN to activate UBA mobile USSD banking on your number. Dial the UBA magic banking code *919#. A welcome message will appear on your mobile screen. Simply dial the USSD *966*0# and follow the onscreen prompts. An account number will be created automatically and sent to you via SMS, the easiest way to get a 50k loan is to use a loan app fair money to be precise. This loan app unlike others, give a larger amount of loan for first time loan seekers. Almost all loan apps in Nigeria give out loans without any documents. All they require is your BVN, and bank details. If you can't make your payments on time, your agreement may require you to pay a fine. The penalties are often outlined in the loans terms and conditions and are applied in the event of a default. Most lenders either increase the interest rate or liquidate the collateral. Before the repayment due date, commonly 7 days before the next monthly repayment, loan companies send a reminder via SMS to notify you of your next repayment. Fair Money loan app calls your number and gives you the option to shift the repayment date. There you have it on the list of USSD code for loans in Nigeria. However, it goes without saying that in order to qualify for an online loan, you must meet certain standards. You'll have to provide your Name, BVN Account Details Address, and more. Additionally, know your credit rate. More importantly, if you don't have a record on your credit history to be impacted, you must be prepared to repay the loan. Did you find this post helpful? Like, share, and don't forget to drop your comment below. Even More Topics: USSD Code for Loans in Nigeria Acquiring a loan usually involves operating an account with a particular bank heading off to the bank, paying your account officer or the banks loan officer a visit, filling out a loan application form, and waiting for your loan to be approved. Hopefully, That's a lot of stress, good news is that now you can easily send a USSD code to get loan information from your preferred loan platform. USSD Code for Loans in Nigeria made it easier for even the poorest of individuals to apply for loan via their mobile devices regardless of whether or not their mobile devices are smart devices or not. Now with this many codes made available, it might be easier to get your loans within a few minutes. However, you shouldn't rush into making loan decisions without comparing loan offers from different lenders before applying for a loan. In this article, we discuss what the USSD platform is, and how you can utilize it to acquire a fast loan in Nigeria. What is USSD? USSD is an acronym that stands for, Unstructured Supplementary Service Data. It can otherwise be known as quick code. As applicable to the name, they are codes used to access options through your mobile telecommunication network provider. USSD can be used for a wide range of things which includes: callback service, content, information, and mobile money or to provide network configuration services. In this case, we consider how the use of USSD in banking. USSD Banking is a type of banking that enables you to make financial transactions from your phone or mobile gadget through the use of short or quick codes. It simply requires a cellular network; no internet connection is required for this transaction. Through USSD banking you could make almost any kind of financial transaction within the loan platforms policy; from making transfers to buying airtime, and utility bill recharge among others. Most importantly, you can use USSD codes to get loans. The steps to applying for a loan from any loan platform via USSD are straightforward and lame and friendly. All you need to do is: Know who you are going to borrow from. Get the functional USSD code for loans in Nigeria include the following: How To Loan Money From GTBank There are two ways to go about it: You can request Quick Credit instantly by dialing *737*51*51# Quick Credit is also available on all GTBank online and mobile banking platforms (Internet Banking, GTWorld, and GTBank Mobile App). How can I get MTN loan? Dial *606# and select XtraTime. You can then select your preferred amount from the list. After selecting your preferred amount, the system will then send you a message with the amount you are about to borrow and the applicable service fee for you to confirm the transaction. With the mobile banking code and Uba quick loan code *919# you can apply for fast online loans without collateral on your registered number with Uba Bank. How do I activate my USSD UBA? To activate and use the UBA mobile banking service without your ATM card, dial the UBA code transfer *919# and then follow the instructions on the screen to get the PIN to activate UBA mobile USSD banking on your number. You then dial the UBA short banking code *919#. A welcome message will pop up on your mobile screen. Simply dial USSD *966*0# and follow the instructions promptly. An account number will be created automatically and sent to you via SMS. What will happen if I wasn't able to pay back at the right time? The Strict penalty that follows being unable to pay back at the right time depends on your agreement. Usually, The penalties are stated in the terms and conditions of the loan and are acted upon once there's a default. Most lenders either increase the interest percentage or sell off collaterals As agreed upon. Looking at the bright side, Carbon (Paylater) does not require collateral and doesn't take brute force in enforcing repayment after the deadline passes. This is why they run a flexible repayment structure that ensures you hardly miss the deadline enabling you to meet up with the repayment deadline. Communications protocol USSD redirects here. For the organization, see United States Society on Dams. USSD on a Sony Ericsson mobile phone (2005) Unstructured Supplementary Service Data (USSD), sometimes referred to as "quick codes" or "feature codes", is a communications protocol used by GSM cellular telephones to communicate with the mobile network operator's computers. USSD can be used for WAP browsing, prepaid callback service, mobile-money services, location-based content services, menu-based information services, and as part of configuring the phone on the network.[1] The service does not require a messaging app, and does not incur charges.[2] USSD messages are up to 182 alphanumeric characters long. Unlike short message service (SMS) messages, USSD messages create a real-time connection during a USSD session. The connection remains open, allowing a two-way exchange of a sequence of data. This makes USSD faster than services that use SMS.[1] While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 ** BS ** 004 ** BS ** 03Change Network passwordNetwork is network dependent, default on some networks is 0000. See call barring functions *33* * 03 * 330 * old password * new password *04Change PIN* * 04 * old PIN * new PIN *04Change PIN2only with Phase 2 SIM* * 042 * old PIN2 * new PIN2 *05Change PIN by PUK* * 05 * PUK * new PIN *05Change PIN2 by PUKonly with Phase 2 SIM* * 052 * PUK * new PIN2 *06Read device number (IMEI)* * 06 #21 unconditional divertall incoming calls will be diverted* * 21 * number * BS ** # 21 ** BS ** # 21 ** BS #30get the called number displayed on the screen when the GSM operator is displayed from a few seconds. While GSM is being phased out in the 2020s with 2G and 3G, a solution is available for supporting USSD services directly from the LTE/5G/IMT networks, providing a similar user experience as in GSM.[10] USSD messages typically start with an asterisk symbol (*) or a hash symbol (#) and is terminated with a hash symbol (#). A typical message comprises digits for commands and data; groups of digits may be separated by additional asterisks.[1] USSD code Mobile-initiated USSD PULL or USSD/PULL when the user dials a code, e.g. *139# from a GSM mobile handset Network-initiated USSD PUSH or USSD/A2P when the user receives a push message from the network; primarily used for promotions. Service Example USSD codes *101*139*1123456789# The codes below are not USSD codes, these are the related Man-Machine Interface (MMI); they are standardized so they are the same on every GSM phone. They are interpreted by the handset first before a corresponding command (not the code itself) is sent to the network. These codes might not always work when using an AT interface; there are standard AT commands defined for each of these actions instead.[11][12] BS is the type of bearer service, some valid values are: 11 for voice 13 for fax 16 for SMS (only valid for barring) 25 for data GSM USSD codes and their functions with various network operators Code Function Note Switch onSwitch offDisplay status02all diversions unconditional, busy, unreachable, does not answer* 002 * number * BS * T * ## 002 ** BS ** 002 ** BS ** 004all conditional redirections, unreachable, does not answer* 004 * number * BS * T * ## 004 **

